After Sales Technical Documentation

Appendix 1 – Transceiver THX–41

Chapter 1

FOREWORD

Original, 09/94

CHAPTER 1 – FOREWORD

CONTENTS

	Page No
Appendix Structure	1–3
Warnings and Cautions	1–3

Appendix Structure

This section of the service manual (Appendix) describes the Nokia THX–41 handportable telephone for use on the Total Access Communications System (TACS). The appendix contains only information specific to the Nokia THX–41 variant.

The appendix comprises three chapters as follows: Chapter 1, Foreword (this chapter); Chapter 2, Transceiver THX–41, containing an exploded view of the THX–41 variant (including a list of assembly parts) plus component parts lists covering the KS3 system module and the KL2 display module; and Chapter 3, Quick Guide, which aims to provide all user information that service personnel are likely to require during servicing and repair of equipment.

IMPORTANT

This document is intended for use by qualified service personnel only.

Warnings and Cautions

Please refer to the phone's user guide for instructions relating to operation, care and maintenance including important safety information. Note also the following:

Warnings:

1. CARE MUST BE TAKEN ON INSTALLATION IN VEHICLES FITTED WITH ELECTRONIC ENGINE MANAGEMENT SYSTEMS AND ANTI–SKID BRAKING SYSTEMS. UNDER CERTAIN FAULT CONDITIONS, EMITTED RF ENERGY CAN AFFECT THEIR OPERATION. IF NECESSARY, CONSULT THE VEHICLE DEALER/MANUFACTURER TO DETERMINE THE IMMUNITY OF VEHICLE ELECTRONIC SYSTEMS TO RF ENERGY.
2. THE HANDPORTABLE TELEPHONE MUST NOT BE OPERATED IN AREAS LIKELY TO CONTAIN POTENTIALLY EXPLOSIVE ATMOSPHERES EG PETROL STATIONS (SERVICE STATIONS), BLASTING AREAS ETC.
3. OPERATION OF ANY RADIO TRANSMITTING EQUIPMENT, INCLUDING CELLULAR TELEPHONES, MAY INTERFERE WITH THE FUNCTIONALITY OF INADEQUATELY PROTECTED MEDICAL DEVICES. CONSULT A PHYSICIAN OR THE MANUFACTURER OF THE MEDICAL DEVICE IF YOU HAVE ANY QUESTIONS. OTHER ELECTRONIC EQUIPMENT MAY ALSO BE SUBJECT TO INTERFERENCE.

Cautions:

1. Servicing and alignment must be undertaken by qualified personnel only.
2. Ensure all work is carried out at an anti–static workstation and that an anti–static wrist strap is worn.
3. Ensure solder, wire, or foreign matter does not enter the telephone as damage may result.
4. Use only approved components as specified in the parts list.
5. Ensure all components, modules screws and insulators are correctly re–fitted after servicing and alignment. Ensure all cables and wires are repositioned correctly.